

# CONNECT

## Product Summary



### Features

- Unframed cubicle system using compact grade laminate
- All edges are polished with radiused corners, for safety
- Soft close aluminium hinges allow doors to fall close quietly, through fixed for added strength.
- Expanding metal inserts are used to accept all hinges
- Through fixed aluminium rotary door lock with no visible fixings and emergency release.
- Adjustable aluminium pedestal using unique clamping system
- Fully extruded aluminium wall channel to rear of each division panel
- Fully extruded aluminium headrail, with no visible fixings for added strength
- Overlap door/panel detail to avoid finger traps



## K32/120A

- Not suitable for Island or free-standing applications, where a fully framed system is vital and recommended.

**Manufacturer:** Prospec Limited, Canklow Meadows Estate, West Bawtry Road, Rotherham, S60 2XL, Tel: 01709 377147, Fax: 01709 375239, Web: [www.prospec.co.uk](http://www.prospec.co.uk) E-mail: [sales@prospec.co.uk](mailto:sales@prospec.co.uk)

**Product reference:** Connect.

**Overall Cubicle Height:** 2006mm including floor clearance of 150mm.

**Frame & Finish:** Aluminium extrusions satin silver anodised to 25 microns.

**Fittings:** Continuous extruded aluminium headrail; extruded aluminium wall channel to rear of each division panel; adjustable pedestal legs with nylon base.

**Door Fittings:** 2N<sup>o</sup> spring loaded, soft closing hinges; satin anodised aluminium door latch with indicator and emergency release to the exterior; rubber buffer sited within the lock receiver; 1 coat hook per cubicle and 2 coat hooks to DDA compliant cubicles.

**Pilasters, Doors & End Panels:** 12mm compact grade laminate.

**Partition Panels:** 12mm compact grade laminate.

**Edge Treatment:** Bull-nosed with radiused corners.

**Colour/Finish:** Select from manufacturer's range availability.

**Accessories:** Door holder for outward opening doors.

Also available in full Height Version up to 2500mm high, including floor clearance from 15mm to 150mm.

