


# CABRILLANT 600

Product Summary



## Features

- Panels from 10mm toughened float glass or 10.76 mm toughened and laminated glass
- Support legs for the 600 system are attached to the front pilaster.
- The Cabrillant frameless system is engineered to disperse stress with emphasis on the method of attaching the friction fit components to the glass, combined with high strength adhesives
- The 25 micron thickness anodised aluminium finish is ideal for use in wet areas
- Cubicles without doors have a small front pilaster to protect the divider panels and are available with PVC anti bacterial curtains
- Available in 16 standard colours. Non-standard colours available on request.



# CABRILLANT 600

Product Summary

## K32/120A

**Manufacturer:** Prospec Limited, Canklow Meadows Estate, West Bawtry Road, Rotherham, S60 2XL, Tel: 01709 377147, Fax: 01709 375239, Web: [www.prospec.co.uk](http://www.prospec.co.uk) E-mail: [sales@prospec.co.uk](mailto:sales@prospec.co.uk)

**Product reference:** Cabrillant 600.

**Overall Cubicle Height:** 2000mm including floor clearance of 150mm as standard, option of 200mm to shower cubicles.

**Frame & Finish:** Aluminium extrusions satin silver anodised to 25 microns.

**Fittings:** Satin anodised aluminium overhead stabilising headrail bar set back 80mm from front face; satin anodised aluminium cubicle support frame brackets and fittings; 2no support legs attached to front pilaster with satin anodised aluminium and stainless steel clamp fixings with adjustable ground clearance.

**Door Fittings:** Satin anodised aluminium spring loaded hinges for automatic opening or closing function; door latch with outside indicator **or** internal aluminium doorknob; DDA compliant door latch with matching grab handles.

**Pilasters, Doors & End Panels:** 10.76mm (2 x 5mm leaves of glass) toughened and laminated glass with a 0.76mm EVA interlayer **or** 10mm toughened float glass **or** 12mm compact grade laminate. Opti-White glass as option.

**Partition Panels:** 10.76mm (2 x 5mm leaves of glass) toughened and laminated glass with a 0.76mm EVA interlayer **or** 10mm Toughened float glass **or** 12mm compact grade laminate. Opti-White glass as option.

**Edge Treatment:** Glass: All edges polished, exposed corners with small radius. Laminate: Bull-nosed with radius corners.

**Colour/Finish:** Glass: Ceramic paint solid colour or etch effect. Choice of 16 standard colours. Non-standard colours available on request. Laminate: Select from manufacturer's range availability.

**Accessories:** External towel rail; coat hooks; hinge and lock blinds on toilet and changing cubicles; all finished in satin anodised aluminium; glass quadrant shower shelves; door holder for outward opening doors; door closers.

